

Nätansluten Värmevarnare

MODEL		GARANTI
ACH11BB	Alkalisk batteribackup (3xAAA)	5 ÅR
ACH11RB	Uppladdningsbart litiumbatteri	5 ÅR

- **FAST FIX** monteringsplatta
- **RF-LINK KOMPATIBEL** utrustad med Radiomodulen (FHN600RF). Säljs separat.
- **TERMISTOR TEKNOLOGI**
- för snabb detektering
- Test/paus med fjärrkontroll tillgänglig
- Låg energiförbrukning (< 0,5 W i standby-läge)



Radio Module
(FHN600RF)
kompatibel



BS 5446-2:2003
KM 654703



TEKNISK SPECIFIKATION	
Matningsspänning	230V ~ – 50Hz.
Reservkraft	ACH11BB – Batteribackup - 3 x AAA-batterier ACH11RB – Förseglat uppladdningsbart litiumbatteri-backup
Larmtyp	Nätansluten värmedetektor
Larmförbindelse (tråd och/eller radio)	Trådbunden sammankoppling eller blandad radiosammankoppling vid montering med Radiomodulen (FHN600RF).
Larmåtgärd	Lågprofilsbas med "Fast-Fix"-funktion eller med reläbas FHN600
Test/Paus	Stor test-/pausknapp, Firehawk FHN600 Remote fjärrkontroll finns också tillgänglig.
Dimensioner	11.3cm (113mm) diameter x 5.5cm (55mm) Djup
Vikt	ACH11BB 180g / ACH11RB 152g
Larmljudnivå	85dB(A) vid 3m
Använd i:	Kök, garage och vind
Platser för installation	Tak
Driftstemperatur	0°C – 40°C
Fuktighet vid drift	< 85% RH
Plastmaterial	ABS-klassad som V-0 enligt UL94
Förpackning	Separat låda och ytterkartong – återvinningsbar kartong.
Huvudförpackning/Ytterkartong	10 st
Max antal anslutna larm	15 via kabel eller 20 via trådlösa/RF-larm
Värmelarmsklass;	Klass A1 värmedetektering 54°–70°C
Godkännande/Certifierad enligt	BS 5446-2 : 2003
Streckkod	ACH11BB – EAN 7332211103250 ACH11RB – EAN 7332211103212
Garanti	5 år (exklusive AAA-batterier)

Deltronic Security AB, EA Rosengrensgata 4, 421 31 Västra Frölunda, Sverige

Tel: 031-140800 | order@deltronic.se | www.deltronic.se

Deltronic reserve the right to change the design or specification details without prior notice.

Mains Powered Heat Alarm

MODEL		WARRANTY
ACH11BB	Alkaline Battery Back-up (3xAAA)	5 YEARS
ACH11RB	Rechargeable Lithium Cell Back-up	5 YEARS

- **FAST FIX** mounting base
- **RF-LINK COMPATIBLE** when fitted with the RF-LINK module (FHN600RF). Sold separately.
- **THERMISTOR TECHNOLOGY**
- Large test/silence button
- Remote control test/silence available
- Low energy usage (< 0.5W in standby mode)



RF-Link Radio Module
(FHN600RF)
compatible



BS 5446-2:2003
KM 654703



TECHNICAL SPECIFICATION	
Supply Voltage	230V ~ – 50Hz.
Back-Up Power	ACH11BB – Battery back-up -3 x AAA batteries ACH11RB – Sealed rechargeable lithium battery back up
Alarm Type	Mains Powered Heat Alarm
Alarm interlink (Wired or RF-Link)	Wired interconnect or mix radio interconnect when fitted with the RF-LINK module (FHN600RF).
Alarm Fixing	Low profile 'Fast-Fix' base or with Relay Base FHN600
Test/Hush	Large Test/Hush button, Firehawk FHN600REMOTE control also available.
Dimensions	11.3cm (113mm) diameter x 5.5cm (55mm) Depth
Weight	ACH11BB 180g / ACH11RB 152g
Alarm Sound level	85dB(A) at 3m
Use in:	Kitchen, Garage and Attic
Installation positions	Ceiling
Operating Temperature	0°C – 40°C
Operating Humidity	< 85% RH
Plastic material	ABS Rated at V-0 against UL94
Packaging	Individual box & outer carton – recyclable cardboard.
Master pack/Outer carton	10 units
Max. num. of connected alarms	15 by cable or 20 by Wireless/RF alarms
Heat Alarm Class;	Class A1 heat detection 54°-70°C
Approval/Certified to	BS 5446-2 : 2003
Barcode	ACH11BB – EAN 7332211103250 ACH11RB – EAN 7332211103212
Warranty	5 years (not including AAA batteries)

Deltronic Security AB, EA Rosengrensgata 4, 421 31 Västra Frölunda, Sweden

Tel: +46-31-140800 | order@deltronic.se | www.deltronic.se

Deltronic reserve the right to change the design or specification details without prior notice.