

XS01-M, XH02-M, XC01-M

Wireless Interlinked Alarms

X-SENSE®
Ultimate Safety Expert



Product Overview

As one of the world's most reliable wireless safety alarms, our wireless smoke alarms are interconnected to each other using radio frequency technology. When one alarm is activated, all other alarms will sound. Moreover, we have introduced the remote controller which can connect with your wireless interconnected network for easy operation and testing purposes. You don't need to use a ladder or stepstool to test/silence your alarm.

The XS01-M Wireless Interlinked Smoke Alarm is designed to comply with the EU standard EN 14604. It can be interconnected with other alarms in a matter of seconds with a simple one-button interconnection process.

The XS01-M smoke alarms that are interconnected will sound if one alarm is triggered, ensuring an immediate response to fire. With the locate function, pressing the test/silence button on any interconnected alarm will silence all but the initiating alarm to quickly find the alarm source.

  EN 14604:2005+AC:2008
Complies with Radio Equipment Directive 2014/53/EU

Product Features

- Compact size matching all the installation environment
- High-performance photoelectric sensor
- Wireless interconnection for the earliest possible warning
- Test/silence all the interlinked alarms in one network
- Interconnects up to 24 wireless alarms
- Low-battery warning
- Loud alert ≥ 85 dB at 3 m
- DC 3 V lithium battery
- Optional wireless remote controller for silencing and testing

Model	Compatible with RC01-Pro:
XS01-M	Wireless interlinked smoke alarm with 3 V lithium battery
XH02-M	Wireless interlinked heat alarm with 3 V built in lithium battery
XC01-M	Wireless interlinked CO alarm with 3 V lithium battery

X-SENSE®
X-Sense Innovations Co., Ltd.



Deltronic

Deltronic Security AB
EA Rosengrängsgata 4
421 31 Västra Frölunda
Sverige
+46-31-140800
www.deltronic.se
info@deltronic.se